

Aluguer de Som

Sistema 1 (interior)

Tope ZXA1 / SUB ELX118P

2.400 wts (RMS)



- Integrated 800 watt power amplifier (500 W RMS)
- Bi-amplified design with transducer protection
- EV8L 8" high-output LF transducer
- DH2005 1" exit true compression driver
- 90° x 50° coverage pattern
- Rotatable horn design
- 126 dB maximum SPL
- Selectable high-pass filter for use with subwoofers
- Line and microphone inputs
- Integral monitor angle on enclosure
- Built-in pole mount
- Lightweight (< 20 lbs) with integral handle for easy carrying



Sistema 2 (interior)

4.800 wts (RMS)



Sistema 3 (interior)

6.800 wts (RMS)



Aluguer de Som

Sistema 1 (exterior)

Line Array 15.000 wts



Topo Line Array- 2 vias

Especificações

Tipo de Coluna Passiva de duas vias

Resposta em Frequência 65Hz - 20.000Hz

Sensibilidade (1W@1m) LF 99dB (Full-Space)

Sensibilidade (1W@1m) HF 108dB (Full-Space)

SPL Maximo Calculado (Cont/Peak) 129dB/132dB (Full-Space)

SPL Maximo Calculado (Cont/Peak) LF 129dB/132dB (Full-Space)

SPL Maximo Calculado (Cont/Peak) HF 132dB/135dB (Full-Space)

Drivers

Médio 1 x 12" (300mm)/3" (76mm) Neodymium,

Agudo 2 x 1.0" (25mm) membrana/1.7" (44mm)

Potência

Program/Peak Power LF 500W/1000W

Program/Peak Power HF 120W/240W

Crossover 2000Hz Linkwitz/Riley 48dB/oct

Crossover Recomendado High-Pass Filter 60Hz, 18dB/oct Butterworth

TECHNICAL SPECIFICATIONS

Nominal diameter.....	460 mm 18 in
Nominal impedance.....	8 Ohm
Minimum impedance.....	5.3 ohm
Power capacity.....	1400 W AES
Program power.....	2800 W
Sensitivity.....	98 dB 1 W @ 1 m
Frequency range.....	25-1800 Hz
Maximum recom. frequency.....	200 Hz
Recommended enclosure volume.....	80 / 200 l 2.8 / 7 ft ³
Voice coil diameter.....	100 mm 4 in
BL factor.....	29 N/A
Moving mass.....	0.230 kg
Winding length.....	25 mm
Air gap height.....	12 mm
Xdamage pp.....	55 mm



Amplificação Powersoft k3

Processador DBX Venu 360

Colunas autónomas Alto Transport 12

6 unidades



Portable Active Speaker

- Battery operated, up to 8 hours operating time
- Loudspeakers: 12/1
- Power: 200W
- Class D amplifier
- Frequency range: 70 / 20,000 Hz
- XLR /jack combo input
- Mic / Line switch
- RCA input
- Built-in USB (MP3/WAV) player
- Wireless microphone
- LC Display
- Built-in castors and trolley-like handle
- 2-Band EQ bass/treble
- 4-point indicator for battery status
- 36 mm speaker flange
- Dimensions: (H x W x D) 609 x 381 x 374 mm
- Weight: 16 kg



Georges  Canário

Musico & Dj



Palco Móvel



Cerimónias Matrimoniais



Animação de rua



Karaoke

Portugal  
Karaoke